

TECHNICAL DATA - FINISHES

Premium Bond™ Stud Adhesive

Premium Bond™ Stud Adhesive is a

water-based synthetic stud adhesive used for bonding plasterboard to timber and metal studs for wall and ceiling linings. Its butter consistency is designed for easy no-slump application, fast grab and maximum adhesive transfer. It is used in a wide range of climatic conditions.



- Easy to use
- Rapid tack
- Tough bond

RECOMMENDED

- Surface preparation Studs should be dry and free of oil and as dust free as possible
- Premium Bond™ Stud Adhesive passes all requirements of the Australian Standard AS2753-1985.
 It is also suitable for application on LOSP (Light Organic Solvent Preservative), CCA and Tanilith treated studs

APPLICATION

- All bonded surfaces should be dry, free of dust, grease, oil or other foreign matter
- Plasterboard linings should be fixed within 30 minutes of adhesive application
- Premium Bond[™] Stud Adhesive must be used in conjunction with nails or screws; it does not constitute a fixing system on its own

INSTALLATION

Refer to USG Boral website **USGBoral.com** or call TecASSIST® on **1800 811 222**.





PREMIUM BOND™ STUD ADHESIVE SPECIFICATIONS

Feature	Description
Colour	Leaf green
Working Time	Drying Type: Bonding time 24-48 hour or longer under adverse conditions
Packaging	Trade 5.2kg (Pail), 600ml (Sausage) DIY 2kg (Pail)
VOC	Less than 50g per litre
Manufacture	Low VOC compound manufactured to stringent USG Boral product quality specifications.
Base	Synthetic Emulsion
рН	8.0-9.0
S.G	1.37 -1.47
Clean Up	Warm soapy water

Premium Bond™ Stud Adhesive

AVOID

 The inclusion of other materials to a mix will impair the performance (e.g. reduced strength and poor adhesion) and void the product warranty

STORAGE

- For optimum shelf life, store tightly sealed pail between 15 and 25°C and out of direct sunlight: do not freeze.
- Premium Bond™ Stud Adhesive should be stored under cover in a dry environment and protected from temperature extremes; storage in an unsuitable environment can shorten the life of this product
- It is recommended that Premium Bond™ Stud Adhesive is used before the best before date displayed on the pails
- It may still be usable after that date if stored unopened, in a suitable environment

DISPOSAL

Please dispose of empty pails and residue in accordance with your local waste management regulations.

HEALTH & SAFETY

- 1. Ensure adequate ventilation. Wear eye protection and rubber gloves to avoid skin contact.
- 2. Do not ingest contents of package. If ingested, seek medical advice immediately.
- 3. Keep contents out of reach of children.
- 4. Be conscious of the environment. Dispose of empty packaging in a responsible manner.

REFERENCES

For further health and safety instructions, refer to the Material Safety Data Sheet for this product, available from your USG Boral sales office, TecASSIST® 1800 811 222 or USGBoral.com

In Emergencies Call **1800 033 111**Poison Information **13 11 26**

SALES ENQUIRIES **1800 003 377** (AU)

TecASSIST[®] **1800 811 222** (AU)

0800 874 267 (NZ)

© 2017 USG BORAL. All rights reserved. The trademarks USG BORAL, INNOVATION INSPIRED BY YOU, TecASSIST and Premium Bond™ Stud Adhesive are trademarks of USG Boral Building Products or one or more of its affiliates.

This technical information is intended to provide general information on plasterboard products and should not be a substitute for professional building advice. Product availability should be checked with your local USG Boral Sales office, as availability may vary.

We recommend you use a qualified person to install USG Boral plasterboard. Illustrations in this guide are only representative of USG Boral plasterboard products and the appearance and effects that may be achieved by their use. To ensure the information you are using is current, USG Boral recommends you review the latest building information available on the USG Boral website. **USGBoral.com**